



**STONEMARKET**



Cromwell - Natural Yorkstone

# Cromwell

A fine-grained hard sandstone quarried from the glacial valleys of Northern England, Cromwell has been used in many prestigious projects since the mid 19th century, including the squares and street schemes of Kensington.

Now available in dimensions ideally suited to domestic applications it has a diamond sawn smooth surface and is an elegant, understated buff with relatively little colour variation. Cromwell comes in 600mm gauge project packs sawn to a 38mm thickness, in random lengths, to create the time-honoured coursed laying pattern associated with this type of stone.

## Cromwell 600mm Gauge Project Pack

minimum m <sup>2</sup> per pack	weight / kg per pack
9*	905*



Thickness 38mm + / -2mm  
\* Project Pack contains 9m<sup>2</sup> made up from random length pieces (600 to 900mm) x 600mm wide



20% Actual Size



Knaresborough



Latitude, Leeds



Bradford



Devonshire Square

#### Colour and Texture Advice

The colours shown are as exact as photographic and printing processes allow. These colourways are intended to give an overall impression of the range of colours that can be found within each product when mixing from three or more packs. They do not give or imply an exact indication of the variations or final proportions of colours found in these products. We encourage that final selection be made from viewing the product laid in a stockist display. In viewing the paving, it should be noted that colour variations and markings are a characteristic of natural stone products. Inherent variation cannot be controlled nor the precise shade of the stone guaranteed. Surface markings can occur in deliveries which may not be seen in a sample. Stone paving may also bear surface markings incurred in the sawing process.



Oxford Road, Ryton on Dunsmore, Warwickshire CV8 3EJ

Tel: 024 7651 8700 Fax: 024 7651 8733

Email: [sales@stonemarket.co.uk](mailto:sales@stonemarket.co.uk)

[www.stonemarket.co.uk](http://www.stonemarket.co.uk)